
Genie® GS™-2669 RT, GS-3369 RT & GS-4069 RT

Specifications

Models	GS-2669 RT		GS-33	69 RT	GS-4069 RT		
Measurements	US	Metric	US	Metric	US	Metric	
Norking height max. ⁽¹⁾	32 ft 2 in	10 m	38 ft 8 in	11.96 m	46 ft 3 in	14.3 m	
A Platform height max.	26 ft 2 in	8 m	32 ft 8 in	9.96 m	40 ft 3 in	12.3 m	
B Platform height - stowed	4 ft 10 in	1.47 m	4 ft 10 in	1.47 m	5 ft 5 in	1.65 m	
D Platform length - outside	9 ft 2 in	2.79 m	9 ft 2 in	2.79 m	9 ft 2in	2.79 m	
Platform length - outside, extended	14 ft 2 in	4.32 m	14 ft 2 in	4.32 m	14 ft 2 in	4.32 m	
Slide-out platform extension deck - length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m	
D Platform width - outside	5 ft 3 in	1.60 m	5 ft 3 in	1.60 m	5 ft 3 in	1.60 m	
Toeboard height	6 in	15 cm	6 in	15 cm	6 in	15 cm	
B Height - stowed (folding rails) ⁽²⁾	8 ft 6 in	2.59 m	8 ft 6 in	2.59 m	9ft	2.74 m	
Height - stowed (rails lowered)	6 ft 3.5 in	1.92 m	6 ft 3.5 in	1.92 m	6 ft 10 in	2.08 m	
Elength machine - stowed	10 ft 3 in	3.12 m	10 ft 3 in	3.12 m	10 ft 3 in	3.12 m	
ength machine - stowed, extended	14 ft 9 in	4.5 m	14 ft 9 in	4.5 m	14 ft 9 in	4.5 m	
ength machine - with outriggers	12 ft 4 in	3.76 m	12 ft 4 in	3.76 m	12 ft 4 in	3.76 m	
G Width	5 ft 9 in	1.75 m	5 ft 9 in	1.75 m	5 ft 9 in	1.75 m	
D Wheelbase	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	
Ground clearance (center)	9.5 in	24 cm	9.5 in	24 cm	9.5 in	24 cm	
Productivity							
Max. platform occupancy (in/out)	4/4		4/2		3/2		
ift capacity	1,500 lb	680 kg	1,000 lb	454 kg	800 lb	363 kg	
ift capacity - extension deck extended	300 lb	136 kg	300 lb	136 kg	300 lb	136 kg	
Nax. platform drive height	26 ft 2 in	5.85 m	32 ft 8 in	9.96 m	40 ft 3 in	12.3 m	
Drive speed - stowed	3.5 mph	5.6 km/h	3.5 mph	5.6 km/h	3.5 mph	5.6 km/h	
Drive speed - raised	0.3 mph	0.5 km/h	0.3 mph	0.5 km/h	0.3 mph	0.5 km/h	
Gradeability - stowed ⁽³⁾	4(0%	35 %		35 %		
īurning radius - inside/outside	83 in/181.2 in	2.11 m/4.6 m	83 in/181.2 in 2.11 m/4.6 m		83 in/181.2 in 2.11 m/4.6 m		
ifting speed - raise/lower	34/31 sec		39/29 sec		61/28 sec		
Filt sensor activation (front to back/side to side)	3°/2°		3°/2°		3°/2°		
Max. outrigger leveling (front to back /side to side)	5.3°/11.7°		5.3°/	/11.7°	5.3°/11.7°		
Drive	40.00'		40.00'		40.00'		
Tires - Foam-filled rough terrain	12×26 in	30×66 cm	12×26 in	30×66 cm	12×26 in	30×66 cm	
Power			Discol		Discol		
Power	Diesel		Diesel		Diesel 07.01		
Fuel Tank	10 gal	37.9L	10 gal	37.9L	10 gal	37.9L	
Hydraulic tank capacity	18 gal	68.1 L	18 gal	68.1L	18 gal	68.1 L	
Neight ⁽⁴⁾ and Floor Loading ⁽⁵⁾	74401	0.0401	7 500 lb	0.4471	10.000 !!	4 74 41-	
Veight	7,149 lb	3,243 kg	7,599 lb	3,447 kg	10,392 lb	4,714 kg	
Neight with outriggers	7,535 lb	3,629 kg	8,449 lb	3,833 kg	11,242 lb	5,100 kg	
Fire load max.	2,840 lb	1,288 kg	3,019 lb	1,369 kg	3,829 lb	1,737 kg	
Fire contact pressure - front, platform fully extended	70.7 psi	487 kPa	75.1 psi	518 kPa	95.3 psi	657 kPa	
Occupied floor pressure	170 psf	8.15 kPa	169 psf	8.11 kPa	215 psf	10.29 kPa	



A



Sound and Vibration Levels

Sound Pressure level (ground workstation)	85 dBA		85 d	BA	85 dBA		
Sound Pressure level (platform workstation)	79 dBA		79 d	BA	79 dBA		
Vibrations	< 8 ft 2 in/s ²	$< 2.5 m/s^2$	< 8 ft 2 in/s ²	$< 2.5 m/s^2$	$< 8 \text{ft} 2 \text{in/s}^2$	$< 2.5 m/s^2$	

The metric equivalent of working height adds 2m to platform height. US adds 6ft to platform height.
 Based on RT tires; deduct 2 in/5.8 cm for turf and non-marking tires.
 Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.
 Weight refers to standard configuration and may vary depending on options and/or country standards.
 Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.







Genie[®] GS[™]-2669 RT, GS-3369 RT & GS-4069 RT

SKU: Standard Model

* Build to Order

- GS266901CF0001: GS-2669 RT, 110V
- GS336901CF0005: GS-3369 RT, 110V
- GS406901CF0003: GS-4069 RT, 110V

SKU: Standard Model

- GS266901CF0004: GS-2669 RT, 220V
- GS336901CF0003: GS-3369 RT, 220V
- GS406901CF0004: GS-4069 RT, 220V

Op	tion availability	S	S+	Bt0	S	Standard		
Power	24.8 hp, 18.5 kW Kubota D1105, Diesel, T4i/T4f, Stage IIIA/V, CN III	 ✓ 	V	V	S+	Standard +		
	Cold weather package		0	0	Bt0	Build to Ore	der	
ď					~	Standard F	eatures	
	Folding rails, Full-height swing gate	v	V	V	О	Options		
	Single slide-out extension deck	 ✓ 	V	V			•	
	Power to platform, no RCBO	× .	~	V			Æ.	
	Power to platform with RCBO		0	0		10		
	Air line to platform			0			~	
Platform	3kW AC Generator, 110V/50Hz		0	0			×	
	3kW AC Generator, 220V/50Hz		0	0	4 W	heel Drive	Full Height Drive	
	AC power to platform	× .	~	V				
	Diamond plate platform deck	× .	~	V				
	Electronic horn	× .	V	V				
	Lanyard attachment points	× .	~	V				
	Link guards (GS-4069)	 ✓ 	V	V				
	Platform control guard (PCON)	× .	~	V		-	<u>_</u>	
	Platform control with fault indicator	× .	~	V		-		
	Platform load sense system	 ✓ 	V	V				
	Proportional drive and lift	× .	~	V				
	Self-closing entry gate	 ✓ 	V	V				
Chassis	Lift Connect Telematics		0	0				-
	Lift Connect with Access Manager upgrade		0	0				
	Eco32 biodegradable hydraulic oil			0				
	Rough Terrain, foam-filled tires	 ✓ 	V	~				
	Rough Terrain, foam-filled, non-marking tires			0	1			-
	4 wheel drive	 ✓ 	V	~	1			-
	Active oscillating axle	 ✓ 	V	V		-		
	Auto leveling hydraulic outriggers	 ✓ 	V	V			-	
	Dual LED flashing beacons	 ✓ 	V	V		A LICE	*	
	Dual wheel multi-disc brakes	 ✓ 	V	V	1		2	
	Hydraulic oil cooler	 ✓ 	V	V		The states		



wing-Out Engine Trav



Genie Genuine Accessories⁽¹⁾

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, evrice marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guord, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries. GEN0951

06/23

WWW.HDW-INTL.COM



Authorise

CE, UKCA