Telescopic Boom Lifts CE, UKCA

Genie® S®-85 XC™

Specifications

Models	S-85 XC	
Measurements	US	Metric
Working height max. ⁽¹⁾	91 ft	27.91 m
Platform height max.	85 ft	25.91 m
Horizontal reach max.	74 ft 6 in	22.71 m
Below ground reach	8 ft 8 in	2.64 m
Platform length (8 ft/6 ft)	3 ft/2 ft 6 in	0.91 m/0.76 m
Platform width (8 ft/6 ft)	8 ft/6 ft	2.44 m/1.83 m
• Height - stowed	9ft 2in	2.80 m
Length - stowed	40 ft 7 in	12.37 m
Length - storage/transport (jib tucked under)	33 ft 8 in	10.25 m
Width	8 ft 2 in	2.49 m
• Wheelbase	9 ft 4 in	2.85 m
G Ground clearance - center	15.8 in	0.40 m
Height under counterweight	3 ft 9 in	1.14 m

Productivity

1 Tourist Tity		
Lift capacity max unrestricted	660 lb	300 kg
Lift capacity max restricted	1,000 lb	454 kg
Number of Platform Occupants (restricted/unrestricted)	3,	/2
Platform rotation	160°	
Jib length	5ft	1.52 m
Vertical jib rotation (up/down)	133°	
Turntable rotation	360°	
Turntable tailswing	5ft 3in	1.60 m
Drive speed - stowed	3.0 mph	4.8 km/h
Drive speed - raised	0.5 mph	0.2 m/s
Gradeability - stowed ⁽²⁾	45 %	
Tilt sensor activation (front to back/side to side)	7°/5°	
Turning radius - inside/outside	12 ft/21 ft 6 in	3.66 m/6.55 m
Tires	18-625	

Power

Power	Diesel	
Hydraulic tank capacity	40 gal	150 L
Fuel tank capacity	35 gal	132L


Weight(3) and Floor Loading(4)


morgine and rivor zodamig		
Weight	39,500 lb	17,917 kg
Tire contact pressure	130 psi	896 kPa
Occupied floor pressure	395 psf	18.9 kPa

Sound and Vibration Levels

Sound Pressure level (ground workstation)	85 dBA
Sound Pressure level (platform workstation)	78 dBA
Vibrations	< 2.5 m/s ²

Range of motion S-85 XC











⁽¹⁾ The metric equivalent of working height adds 2m to platform height. The imperial equivalent adds 6ft to

⁽¹⁾ The Heithe equivalent of working height adds 21th to platform height. The imperial equivalent adds of to platform height.
(2) Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.
(3) Weight refers to standard configuration and may vary depending on options and/or country standards.
(4) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.

Telescopic Boom Lifts CE, UKCA

Genie® S®-85 XC™

SKU: Standard Model

- \$85XC001CV0028: S-85 XC, 220V, 4WD, Control box covers
- **\$85XC001Cl0004:** S-85 XC, Stage IIIA, 220V, Engine gauge, 4WD
 - * Build to Order

SKU: Standard Model

- S85XC001CV0031: S-85 XC, 110V, 4WD
- **\$85XC001CV0001:** S-85 XC, 220V, 4WD
- \$85XC001Cl0030: S-85 XC, 110V, Lift Power 3kW, 4WD
- \$85XC001CV0029: S-85 XC, 220V, Lift Power 3kW, 4WD

0	lian availahilih.	0.	DAO
Up	tion availability S	S+	Bt0
	74 hp, 55 kW, Deutz TD2011, Turbo Diesel, T4i/Stage IIIA/CN III		0
	74 hp, 55 kW, Deutz TCD2.2L, Turbo Diesel, Stage V		V
	Cold weather package	0	0
Power	Diesel air intake pre-cleaner		0
ò	Diesel catalytic scrubber muffler (T4i/Stage IIIA/CN III)		0
"	Positive air shutdown system	V	0
	Anti-restart engine protection Auto engine fault shutdown		
	In cylinder glow plug (diesel only)		
	6ft/1.83m dual-entry platform with side swing gate		0
	8ft/2.44m tri-entry platform with side swing gate		· /
	Power to platform, no RCBO		V
	Power to platform with RCBO	0	0
	Dual axis joystick steering		0
	Thumb rocker steering Air line to platforms	V	V
	Air line to platform Control box covers	0	0
	Lift Guard Full Mesh panels		0
_	Lift Guard Half Mesh panels		0
Platform	Light Package: drive and work lights		
ig	Platform auxiliary top rail		0
P	Lift Power 3kW AC Generator, 110V/50Hz		0
	Lift Power 3kW AC Generator, 220V/50Hz		O
	660lb/300kg & 1000lb/454kg dual load capacity with automatic envelope control	V	1
	Drive enable system	V	V
	Horn		V
	Lift Guard Contact Alarm	V	V
	Lift Tools Work Tray	V	V
	Platform load sense system	V	V
	Proportional controls	V	V
	Self-leveling platform	V	V
	Lift Connect Telematics	V	· /
	Lift Connect with Access Manager upgrade	0	0
	Eco32 biodegradable hydraulic oil	0	0
	Rough terrain, foam-filled tires	V	V
	Rough terrain, foam-filled, non-marking tires		0
	Deluxe hostile environment kit		0
	Hostile environment kit		0
<u>.s</u>	Chassis tilt lift function cut-out	0	0
Chassis	Tow package		0
ha	Active oscillating axle		V
O	Alarm package: includes flashing beacon and travel alarm		V
	Descent, tilt and motion alarm	_	V
	Dual battery system		
	Hour meter v	_	
	Hydraulic oil cooler	_	V
	Positive traction drive	_	<u> </u>
	Tech Pro Link connector		
	Wheel motors 2 speed	V	V

Positive air shutdown system for Stage V only

S Standard
S+ Standard +
Bt0 Build to Order
Standard Features
Options







Xtra Capacity

Rugged Terrainability

Lift Power



Genie Genuine Accessories(1)

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

06/23 GEN2930



WWW.HDW-INTL.COM

