Telescopic Boom Lifts CE, UKCA

# enie® SX™-105 XC™ & SX-125 XC

### **Specifications**

Models	SX-105 XC		SX-125 XC	
Measurements	US	Metric	US	Metric
Working height max. <sup>(1)</sup>	111 ft	34,00 m	131 ft	40,10 m
Platform height max.	105 ft	32,00 m	125 ft	38,10 m
Horizontal reach max.	80 ft	24,38 m	80 ft	24,38 m
Below ground reach	8 ft 10 in	2,69 m	8 ft 10 in	2,69 m
Platform length (8 ft/6 ft)	3 ft/2 ft 6 in	0,91 m/0,76 m	3 ft/2 ft 6 in	0,91 m/0,76 m
B Platform width (8 ft/6 ft)	8 ft/6 ft	2,44 m/1,83 m	8 ft/6 ft	2,44m/1,83m
• Height - stowed	10ft	3,05 m	10ft	3,05 m
<ul><li>Length - stowed</li></ul>	46 ft 9 in	14,25 m	46ft 9in	14,25 m
<ul><li>Length - storage/transport (jib tucked under)</li></ul>	40 ft	12,19 m	40 ft	12,19 m
Width (axles retracted)	8ft 2in	2,49 m	8ft 2in	2,49 m
Width (axles extended)	12 ft 11 in	3,94 m	12 ft 11 in	3,94 m
Wheelbase	13 ft 6 in	4,11 m	13ft 6 in	4,11 m
G Ground clearance - center	15 in	0,38 m	15 in	0,38 m
1 Height under counterweight	3 ft 11 in	1,19 m	4ft	1,22 m

### **Productivity**

Troductivity				
Lift capacity max unrestricted	660 lb	300 kg	660 lb	300 kg
Lift capacity max restricted	1 000 lb	454 kg	1 000 lb	454 kg
Number of Platform Occupants (restricted/unrestricted)	3/2		3/2	
Platform rotation	160°		160°	
Jib length	5 ft	1,52 m	5ft	1,52 m
Vertical jib rotation (up/down)	135°		135°	
Turntable rotation	360°		360°	
Turntable tailswing (axles retracted)	1 ft 10 in	0,56 m	1 ft 10 in	0,56 m
Turntable tailswing (axles extended)	3 ft 4 in	1,02 m	3ft 4in	1,02 m
Drive speed - stowed	3,0 mph	4,9 km/h	3,0 mph	4,9 km/h
Drive speed - raised	0,38 mph	0,6 km/h	0,38 mph	0,6 km/h
Gradeability - stowed(2)	40 %		40 %	
Tilt sensor activation (front to back/side to side)	4,5°/3°		4,5°/3°	
Turning radius - inside/outside (axle retracted)	26 ft 4 in/	8,03 m/	26 ft 4 in/	8,03 m/
	32 ft 8 in	9,96 m	32 ft 8 in	9,96 m
Turning radius - inside/outside (axle extended)	9ft 6in/	2,90 m/	9ft 6in/	2,90 m/
	20 ft 3 in	6,17 m	20 ft 3 in	6,17 m
Tires	385/65D22.5		445D50/710	

## **Power**

Power	Diesel		Diesel	
Hydraulic tank capacity	55 gal	208 L	55 gal	208 L
Fuel tank capacity	40 gal	151 L	40 gal	151 L


# Weight(3) and Floor Loading(4)

Weight	41 017 lb	18 605 kg	45 636 lb	20 700 kg
Tire contact pressure	102 psi	700 kPa	102 psi	700 kPa
Occupied floor pressure, axles retracted/ extended	291 psf/	13,93 kPa/	324 psf/	15,52 kPa/
	184 psf	8.81 kPa	205 psf	9.81 kPa


# **Sound and Vibration Levels**


Sound Pressure level (ground workstation)	91 dBA	91 dBA
Sound Pressure level (platform workstation)	75 dBA	75 dBA
Vibrations	< 2,5 m/s <sup>2</sup>	< 2,5 m/s <sup>2</sup>


#### Range of motion SX-105 XC



# Range of motion SX-125 XC











platform height.
(2) Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.

(3) Weight refers to standard configuration and may vary depending on options and/or country standards.

<sup>(4)</sup> Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.





Telescopic Boom Lifts CE, UKCA

# Genie® SX™-105 XC™ & SX-125 XC

#### SKU: Standard Model

- SX105XC1Cl0020: SX-105 XC, Stage IIIA, 220V, 4WD, Control box covers
- **SX105XC1CV0017:** SX-105 XC, Stage V, 110V, 4WD, Control box covers
- SX105XC1CV0019: SX-105 XC, Stage V, 220V, 4WD, Control box covers
- SX105XC1CV0018: SX-105 XC, Stage V, 220V, 3kW Generator, 4WD, Control box covers
  - \* Build to Order

#### SKU: Standard Model

- SX125XC1Cl0028: SX-125 XC, Stage IIIA, 220V, 4WD, Control box covers
- SX125XC1CV0047: SX-125 XC, Stage V, 110V, 4WD, Control box covers
- SX125XC1CV0045: SX-125 XC, Stage V, 110V, 3kW Generator, 4WD, Control box covers
- **SX125XC1CV0046:** SX-125 XC, Stage V, 220V, 4WD, Control box covers
- SX125XC1CV0048: SX-125 XC, Stage V, 220V, 3kW Generator, 4WD, Control box covers









**Xtra Capacity** 



#### Genie Genuine Accessories(1)

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.



- Option availability S S+ BtO 74 hp, 55 kW, Deutz TD2011, Turbo Diesel, T4i/Stage IIIA/CN III 74 hp, 55 kW, Deutz TCD2.2L, Turbo Diesel, Stage V Cold weather package Diesel air intake pre-cleaner Diesel catalytic scrubber muffler (T4i/Stage IIIA/CN III) Positive air shutdown system Anti-restart engine protection Auto engine fault shutdown In cylinder glow plug (diesel only) 6ft/1,83m dual-entry platform with side swing gate 8ft/2,44m tri-entry platform with side swing gate Power to platform, no RCBO Power to platform with RCBO Dual axis joystick steering Thumb rocker steering Air line to platform Control box covers Lift Guard Full Mesh panels Lift Guard Half Mesh panels Light Package: drive and work lights Platform auxiliary top rail 3kW AC Generator, 110V/50Hz 3kW AC Generator, 220V/50Hz 4 Steering modes 660lb/300kg & 1000lb/454kg dual load capacity with automatic envelope control Drive enable system Horn Lift Guard Contact Alarm Lift Tools Work Tray ~ Platform load sense system Proportional controls Self-leveling platform **Lift Connect Telematics** Telematics-ready Lift Connect with Access Manager upgrade Eco32 biodegradable hydraulic oil Rough terrain, foam-filled tires Hostile environment kit Chassis tilt lift and drive function cut-out 2 speed wheel motors Alarm package: includes flashing beacon and travel alarm Chassis tilt drive function cut-out ~ Descent, tilt and motion alarm Dual battery system ~ Hour meter ~ Hydraulic oil cooler Mini XChassis extendable axles V Positive traction drive Tech Pro Link connector

Positive air shutdown system for Stage V only



