Genie[®] SX[™]-135 XC[™]

Specifications

Models	SX-135 XC		
Measurements	US	Metric	
Working height max. ⁽¹⁾	141 ft	43.15 m	
Platform height max.	135 ft	41.15 m	
Horizontal reach max.	90 ft	27.43 m	
Below ground reach	19 ft 8 in	6.00 m	
A Platform length	3 ft	0.91 m	
B Platform width	8 ft	2.44 m	
C Height - stowed	10ft	3.05 m	
Length - stowed	64 ft 10 in	19.76 m	
Length - storage/transport (jib tucked under)	43 ft 7 in	13.28 m	
Width (axles retracted)	8 ft 2 in	2.49 m	
Width (axles extended)	12ft 11 in	3.94 m	
Wheelbase (axles retracted)	13 ft 6 in	4.11 m	
Wheelbase (axles extended)	13 ft 6 in	4.11 m	
G Ground clearance - center	15 in	0.38 m	
Height under counterweight	4 ft 1 in	1.24 m	

Productivity

Lift capacity max unrestricted	660 lb	300 kg	
Lift capacity max restricted	1,000 lb	454 kg	
Number of Platform Occupants (restricted/unrestricted)	3/2		
Platform rotation	160°		
Jib length	18/30ft	5.48/9.14 m	
Vertical jib rotation (up/down)	130°		
Turntable rotation	360°		
Turntable tailswing (axles retracted)	3 ft 9 in	1.14 m	
Turntable tailswing (axles extended)	5 ft 7 in	1.70 m	
Drive speed - stowed	2.7 mph	4.3 km/h	
Drive speed - raised	0.4 mph	0.65 km/h	
Gradeability - stowed ⁽²⁾	35 %		
Tilt sensor activation (front to back/side to side)	4.5°/4.5°		
Turning radius - inside/outside (axle retracted)	26 ft 4 in/32 ft 8 in	8.03 m/9.96 m	
Turning radius - inside/outside (axle extended)	9 ft 6 in/20 ft 3 in	2.90 m/6.17 m	
Tires	445D50/710		

Power

Power	Diesel	Diesel		
Hydraulic tank capacity	60 gal	227 L		
Fuel tank capacity	40 gal	151 L		
Fuel tank capacity	40 gal	151 L		


Weight⁽³⁾ and Floor Loading⁽⁴⁾

Weight	46,900 lb	21,273 kg		
Tire contact pressure	130 psi	896 kPa		
Occupied floor pressure, axles retracted/ extended	351 psf/ 222 psf	16.79 kPa/ 10.62 kPa		


Sound and Vibration Levels

Sound Pressure level (ground workstation)	91 dBA
Sound Pressure level (platform workstation)	75 dBA
Vibrations	< 2.5 m/s ²

Range of motion SX-135 XC









(1) The metric equivalent of working height adds 2m to platform height. The imperial equivalent adds 6ft to platform height. (2) Gradeability applies to driving on slopes and may vary depending on options and machine configurations.

(2) Gradeability applies to thirting on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.
 (3) Weight refers to standard configuration and may vary depending on options and/or country standards.
 (4) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.





Genie[®] SX[™]-135 XC[™]

SKU: Standard Model

• SX-135 XC, 4WD*

- SX135XC1Cl0020: SX-135 XC, Stage IIIA, 220V, 4WD, Control Box Covers
 - * Build to Order

SKU: Standard Model

- SX135XC1CV0030: SX-135 XC, Stage V, 110V, 4WD, Control Box Covers
- SX135XC1CV0026: SX-135 XC, Stage V, 110V, 3kW Generator, 4WD, Control Box Covers
- SX135XC1CV0031: SX-135 XC, Stage V, 220V, 4WD, Control Box Covers
- SX135XC1CV0032: SX-135 XC, Stage V, 220V, 3kW Generator, 4WD, **Control Box Covers**

Standard Features

Op	tion availability	S	S+	Bt0	S	Standard
	74 hp, 55 kW, Deutz TD2011, Turbo Diesel, T4i/Stage IIIA/CN III			0	S+	Standard +
Power	74 hp, 55 kW, Deutz TCD2.2L, Turbo Diesel, Stage V	V	V	~	Bt0	Build to Order
	Cold weather package		0	0	~	Standard Feat
	Diesel air intake pre-cleaner			0	0	Options
	Diesel catalytic scrubber muffler (T4i/Stage IIIA/CN III)			0	0	optiono
P	Positive air shutdown system			0		
	Anti-restart engine protection	V	V	~		
	Auto engine fault shutdown	~	V	V		
	In cylinder glow plug (diesel only)	· ·	V	V		
	6ft/1.83m dual-entry platform with side swing gate			0		ib-Extend 0
	8ft/2.44m tri-entry platform with side swing gate	V	V	~	18-30	ft/5.48-9.14m
	Power to platform, no RCBO	 ✓ 	V	V		
	Power to platform with RCBO		0	0		
	Dual axis joystick steering			0		
	Thumb rocker steering	V	V	~		Course of
	Air line to platform			0		5 Y
	Control box covers		V		1	
	Lift Guard Full Mesh panels			0		AL ST
E	Lift Guard Half Mesh panels			0		
Platform	Light Package: drive and work lights			0		
atf	3kW AC Generator, 110V/50Hz			0		
Ē	3kW AC Generator, 220V/50Hz			0		
	4 Steering modes	v	V	~		
	660lb/300kg & 1000lb/454kg dual load capacity with automatic envelope control	 ✓ 	V	V		
	Drive enable system	~	V	V		
	Horn	 ✓ 	V	V		
	Lift Guard Contact Alarm	v	V	V		
	Lift Tools Work Tray	 ✓ 	V	V		
	Platform load sense system	 Image: A start of the start of	V	V		
	Proportional controls	 Image: A start of the start of	V	V		
	Self-leveling platform	~	V	V		
	Lift Connect Telematics	v	V	V		AL-S
	Telematics-ready	 ✓ 	V	V		
	Lift Connect with Access Manager upgrade		0	0		
	Eco32 biodegradable hydraulic oil			0		
	Rough terrain, foam-filled tires	V	V	V		
	Hostile environment kit			0		
	Chassis tilt lift and drive function cut-out		0	0	R	
SiS.	2 speed wheel motors	V	V	V		
Chassis	Alarm package: includes flashing beacon and travel alarm	 ✓ 	V	V		
- Å	Chassis tilt drive function cut-out	 ✓ 	V	V	-	
	Descent, tilt and motion alarm	 Image: A start of the start of	V	V	Ger	nie Genuine
	Dual battery system	v	V	V		
	Hour meter	v	V	V	• Lif	t Tools Productiv
	Hydraulic oil cooler	v	V	V	• iff	t Connect Telem
	Mini XChassis extendable axles	v	V	V		ch Pro Link Han
	Positive traction drive	v	V	V	• 160	IT PTO LITIK HAN
	Tech Pro Link connector	v	V	V	(1) Mor	e accessories available

Positive air shutdown system for Stage V only





Genie Genuine Accessories⁽¹⁾

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

06/23

GEN0182



WWW.HDW-INTL.COM

