Technical sheet:


ULM 412 H







A 111		
Capacities	Metric	Imperial
Max. capacity	Q 1250 kg	2756 lb
Max. lifting height	h3 4.30 m	14 ft 1 in
Max. outreach	2.62 m	8 ft 7 in
Reach at max. height	1 m	3 ft 3 in
Breakout force with bucket	1880 daN	1880 daN
Weight and dimensions		
Shipping mass (min. / max.)	2550 kg / 2750 kg	5622 lb / 6063 lb
Ground clearance	m4 0.29 m	11 in
Wheelbase	y 2.13 m	7 ft
Overall length to carriage (with hitch)	3.47 m	11 ft 5 in
Overall length to carriage (without hitch)	13 3.47 m	11 ft 5 in
Front overhang	0.77 m	2 ft 6 in
Overall width	b1 1.49 m	4 ft 11 in
Overall cab width	b4 0.66 m	2 ft 2 in
		6 ft 4 in
•	117 1.92 m	
Tilt-down angle	a5 116 °	116 °
Tilt-up angle	a4 23 °	23 °
	Va1 2.62 m	8 ft 7 in
Standard tyres	CAMSO - MPT 552 - 10.0/75-15.3 124A8	CAMSO - MPT 552 - 10.0/75-15.3 124A8
Performances		
Lifting	8.80 s	8.80 s
Lowering	7 s	7 s
Extension	6.40 s	6.40 s
Retraction	4.30 s	4.30 s
Crowd	3.40 s	3.40 s
Dump	2.60 s	2.60 s
Engine		
Engine brand	Yanmar	Yanmar
Engine norm	Stage V / Tier 4 final	Stage V / Tier 4 final
Engine model	3TNV88C-DMU	3TNV88C-DMU
Number of cylinders - Capacity of cylinders	3 - 1642 cm³	3 - 100 in³
I.C. Engine power rating / Power (kW)	35.10 Hp / 26.20 kW	35.10 Hp / 26 kW
Max. torque / Engine rotation	105 Nm @1950 rpm	77 ft/lbs @1950 rpm
Drawbar pull (Laden)	2000 daN	2000 daN
Reversible fan	Option	Option
	3 radiators (water + hydraulic oil + fuel)	3 radiators (water + hydraulic oil + fuel)
Engine cooling system	3 laulatois (water + liyulaulic oii + luer)	3 ladiators (water + flydiadiic off + fder)
Transmission	Understalle	Understation
Transmission type	Hydrostatic	Hydrostatic
Number of gears (forward / reverse)	2/2	2/2
Max. travel speed (may vary according to applicable regulations)	25 km/h	16 mi/h
Differential lock	Limited slip differential on front and rear axles	Limited slip differential on front and rear axle
Parking brake	Automatic negative parking brake	Automatic negative parking brake
Service brake	Hydraulic servo brake	Hydraulic servo brake
Hydraulics		
Hydraulic pump type	Gear pump	Gear pump
Hydraulic flow - Pressure	48 I/min - 235 bar	13 US gpm - 3408 PSI
Flow sharing distributor	Standard	Standard
Tank capacities		
Hydraulic oil	39	10 US gal
Fuel tank	35 I	9 US gal
Noise and vibration		
Noise at driving position (LpA) tested following NF EN 12053 norm	76 dB	76 dB
Environmental noise (LwA)	104 dB	104 dB
Vibration to whole hand/arm	< 2.50 m/s²	< 2.50 m/s ²
	< 2.50 III/S²	< 2.50 III/S*
	the state of the s	
Miscellaneous Safety cab homologation	Cabin ROPS - FOPS Level 1	Cabin ROPS - FOPS Level 1

ULM 412 H - Dimensional drawing








ULM 412 H - Load chart

Machine on tyres with forks Metric

Machine on tyres with forks Imperial







Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes